

产品性能参数及选型代码

额定速度	轴高	电机订货号	额定功率	额定转矩	额定电流	额定电压	最大可控转速	最大转速	堵转转矩	效率	堵转电流	额定频率	转动惯量
n_{rated} rpm	SH mm	Order No.	P_{rated} Kw	M_{rated} Nm	I_{rated} A	U_{rated} V	$n_{max\ Inv}$ rpm	n_{max} rpm	M_0 Nm	η	I_0 A	F_{rated} Hz	J kgm ²
进线电压:3相400V, 电源模块:Smart/Basic Line module													
700	180	1PH8184-2□□□□-□□□ 1	33	450	80	278	1450	3800	480	93.2	84	47.0	0.46
		1PH8186-2□□□□-□□□ 1	44	600	108	269	1450	3800	640	92.4	115	47.0	0.60
	225	1PH8224-2□□□□-□□□ 1	48	655	120	256	1450	3500	708	96.1	128	47.0	1.28
		1PH8226-2□□□□-□□□ 1	64	873	170	238	1550	3500	944	96.3	183	47.0	1.66
1000	180	1PH8228-2□□□□-□□□ 1	80	1091	200	254	1450	3500	1180	96.5	213	47.0	2.02
		1PH8184-2□□□□-□□□ 1	46	439	106	285	1950	3800	480	93.7	115	67.0	0.46
	225	1PH8186-2□□□□-□□□ 1	62	592	148	275	2050	3800	640	94.3	157	67.0	0.60
		1PH8224-2□□□□-□□□ 1	68	649	170	254	2050	3500	708	96.4	183	67.0	1.28
1500	180	1PH8226-2□□□□-□□□ 1	91	869	215	265	1950	3500	944	96.7	233	67.0	1.66
		1PH8228-2□□□□-□□□ 1	113	1079	265	271	1950	3500	1180	96.8	284	67.0	2.02
	132	1PH8131-2□□□□-□□□ 1	15.7	100	29	388	2550	4500	105	0.944	30	50.0	0.0446
		1PH8133-2□□□□-□□□ 1	19.9	127	44	316	3050	4500	131	0.948	45	50.0	0.0600
2000	160	1PH8135-2□□□□-□□□ 1	23.7	151	43	383	2450	4500	158	0.952	44	50.0	0.0750
		1PH8137-2□□□□-□□□ 1	30.6	195	60	356	2700	4500	203	0.952	62	50.0	0.0885
	180	1PH8165-2□□□□-□□□ 1	61	390	119	340	2600	4000	440	0.940	126	100.0	0.2160
		1PH8167-2□□□□-□□□ 1	69	435	133	345	2600	4000	500	0.940	143	100.0	0.2440
2500	225	1PH8184-2□□□□-□□□ 1	70	446	148	308	2700	3800	480	95.1	157	100	0.46
		1PH8186-2□□□□-□□□ 1	93	592	215	282	2950	3800	640	95.2	229	100	0.60
	132	1PH8224-2□□□□-□□□ 1	101	643	235	271	2900	3500	708	96.5	256	100	1.28
		1PH8226-2□□□□-□□□ 1	134	853	295	288	2700	3500	944	96.7	320	100	1.66
3000	160	1PH8228-2□□□□-□□□ 1	168	1070	395	270	2900	3500	1180	96.7	427	100	2.02
		1PH8135-2□□□□-□□□ 1	31.4	150	59	356	3500	4500	158	0.953	63	66.7	0.0750
	132	1PH8131-2□□□□-□□□ 1	25	96	44	371	4050	4500	105	0.948	48	83.3	0.0446
		1PH8133-2□□□□-□□□ 1	31.7	121	55	371	3950	4500	131	0.951	59	83.3	0.0600
3300	160	1PH8137-2□□□□-□□□ 1	48.4	185	83	371	3900	4500	203	0.954	89	83.3	0.0885
		1PH8165-2□□□□-□□□ 1	84	320	148	370	3900	4000	440	0.955	188	167.0	0.2160
	132	1PH8167-2□□□□-□□□ 1	95	360	177	350	4000	4000	500	0.955	230	167.0	0.2440
		1PH8137-2□□□□-□□□ 1	57.5	183	104	370	4500	4500	203	0.953	115	100.0	0.0885
进线电压:3相400V, 电源模块:Active Line module													
800	180	1PH8131-2□□□□-□□□ 1	38	454	80	316	1450	3800	480	92.6	84	53.0	0.46
		1PH8186-2□□□□-□□□ 1	50	597	108	306	1450	3800	640	93.1	115	53.0	0.60
	225	1PH8224-2□□□□-□□□ 1	55	657	120	292	1450	3500	708	96.2	128	53.0	1.28
		1PH8226-2□□□□-□□□ 1	73	871	170	271	1550	3500	944	96.5	183	53.0	1.66
1150	180	1PH8228-2□□□□-□□□ 1	91	1086	198	290	1450	3500	1180	96.7	213	53.0	2.02
		1PH8184-2□□□□-□□□ 1	53	440	106	327	1950	3800	480	94.2	115	77.0	0.46
	225	1PH8186-2□□□□-□□□ 1	71	590	148	315	2050	3800	640	94.8	157	77.0	0.60
		1PH8224-2□□□□-□□□ 1	78	648	170	292	2050	3500	708	96.5	183	77.0	1.28
1750	132	1PH8226-2□□□□-□□□ 1	104	864	215	304	1950	3500	944	96.7	233	77.0	1.66
		1PH8228-2□□□□-□□□ 1	129	1071	260	311	1950	3500	1180	96.9	284	77.0	2.02
	160	1PH8131-2□□□□-□□□ 1	18	98	29	415	2550	4500	105	0.947	30	58.3	0.0446
		1PH8133-2□□□□-□□□ 1	23.1	126	43	366	3050	4500	131	0.950	45	58.3	0.0600
2300	180	1PH8135-2□□□□-□□□ 1	27.2	149	42	415	2450	4500	158	0.952	44	58.3	0.0750
		1PH8137-2□□□□-□□□ 1	35.6	194	59	412	2700	4500	203	0.953	62	58.3	0.0885
	225	1PH8165-2□□□□-□□□ 1	69	375	115	395	2600	4000	440	0.943	126	117.0	0.2160
		1PH8167-2□□□□-□□□ 1	77	420	128	400	2600	4000	500	0.943	143	117.0	0.2440
2800	132	1PH8184-2□□□□-□□□ 1	82	447	150	359	2700	3800	480	95.4	157	117	0.46
		1PH8186-2□□□□-□□□ 1	109	595	215	328	2950	3800	640	95.5	229	117	0.60
	160	1PH8224-2□□□□-□□□ 1	117	638	235	315	2900	3500	708	96.5	256	117	1.28
		1PH8226-2□□□□-□□□ 1	156	851	295	335	2700	3500	944	96.6	320	117	1.66
3300	132	1PH8228-2□□□□-□□□ 1	195	1064	390	314	2900	3500	1180	96.6	427	117	2.02
		1PH8135-2□□□□-□□□ 1	35.6	148	59	407	3500	4500	158	0.953	63	76.7	0.0750
	160	1PH8131-2□□□□-□□□ 1	27.7	95	44	415	4050	4500	105	0.949	48	93.3	0.0446
		1PH8133-2□□□□-□□□ 1	35.2	120	54	415	3950	4500	131	0.952	59	93.3	0.0600
3300	132	1PH8137-2□□□□-□□□ 1	53.4	182	82	415	3900	4500	203	0.953	89	93.3	0.0885
		1PH8165-2□□□□-□□□ 1	87	300	138	410	3900	4000	440	0.959	188	187.0	0.2160
	160	1PH8167-2□□□□-□□□ 1	98	335	164	385	4000	4000	500	0.959	230	187.0	0.2440
		1PH8137-2□□□□-□□□ 1	62.2	180	102	405	4500	4500	203	0.952	115	110.0	0.0885

永磁同步伺服电机

1PH8 同步伺服电机
强迫风冷，防护等级 IP55

产品性能参数及选型代码

额定速度	轴高	电机订货号	额定功率	额定转矩	额定电流	额定电压	最大可控转速	最大转速	堵转转矩	效率	堵转电流	额定频率	转动惯量
n_{rated} rpm	SH mm	Order No.	P_{rated} Kw	M_{rated} Nm	I_{rated} A	U_{rated} V	$n_{max Inv}$ rpm	n_{max} rpm	M_0 Nm	η	I_0 A	F_{rated} Hz	J kgm ²
进线电压:3相480V, 电源模块:Smart/Basic/Active Line module													
1000	180	1PH8184-2□C□□-□□□ 1	46	439	78	390	1450	3800	480	93.7	84	67.0	0.46
		1PH8186-2□C□□-□□□ 1	62	592	108	379	1450	3800	640	94.1	115	67.0	0.60
	225	1PH8224-2□C□□-□□□ 1	68	649	118	363	1450	3500	708	96.5	128	67.0	1.28
		1PH8226-2□C□□-□□□ 1	91	869	170	338	1550	3500	944	96.7	183	67.0	1.66
1350	180	1PH8228-2□C□□-□□□ 1	113	1079	198	361	1450	3500	1180	96.8	213	67.0	2.02
		1PH8184-2□D□□-□□□ 1	62	439	106	382	1950	3800	480	94.6	115	90.0	0.46
	225	1PH8186-2□D□□-□□□ 1	83	587	146	368	2050	3800	640	95.2	157	90.0	0.60
		1PH8224-2□D□□-□□□ 1	91	644	168	342	2050	3500	708	96.5	183	90.0	1.28
2000	132	1PH8226-2□D□□-□□□ 1	121	856	215	356	1950	3500	944	96.8	233	90.0	1.66
		1PH8228-2□D□□-□□□ 1	151	1068	260	364	1950	3500	1180	96.8	284	90.0	2.02
	160	1PH8131-2□F□□-□□□ 1	19.9	95	29	449	2550	4500	105	0.948	30	66.7	0.0446
		1PH8133-2□F□□-□□□ 1	26.2	125	43	415	3050	4500	131	0.951	45	66.7	0.0600
		1PH8135-2□F□□-□□□ 1	30.2	144	42	449	2450	4500	158	0.953	44	66.7	0.0750
		1PH8137-2□F□□-□□□ 1	40.0	191	59	449	2700	4500	203	0.954	62	66.7	0.0885
	180	1PH8165-2□F□□-□□□ 1	74	355	110	445	2600	4000	440	0.946	126	133.0	0.2160
		1PH8167-2□F□□-□□□ 1	82	395	123	450	2600	4000	500	0.946	143	133.0	0.2440
	225	1PH8184-2□F□□-□□□ 1	86	411	138	404	2700	3800	480	95.7	157	133	0.46
		1PH8186-2□F□□-□□□ 1	115	549	200	370	2950	3800	640	95.6	229	133	0.60
		1PH8224-2□F□□-□□□ 1	118	563	210	355	2900	3500	708	96.3	256	133	1.28
		1PH8226-2□F□□-□□□ 1	157	750	260	378	2700	3500	944	96.4	320	133	1.66
2650	132	1PH8228-2□F□□-□□□ 1	196	936	345	355	2900	3500	1180	96.4	427	133	2.02
		1PH8135-2□G□□-□□□ 1	40.2	145	58	449	3500	4500	158	0.952	63	88.3	0.0750
	160	1PH8131-2□L□□-□□□ 1	29.5	94	43	449	4050	4500	105	0.951	48	100.0	0.0446
		1PH8133-2□L□□-□□□ 1	37.4	119	54	449	3950	4500	131	0.952	59	100.0	0.0600
3000	132	1PH8137-2□L□□-□□□ 1	56.9	181	81	449	3900	4500	203	0.953	89	100.0	0.0885
		1PH8165-2□L□□-□□□ 1	89	285	131	440	3900	4000	440	0.960	188	200.0	0.2160
	160	1PH8167-2□L□□-□□□ 1	99	315	155	410	4000	4000	500	0.960	230	200.0	0.2440
		1PH8137-2□M□□-□□□ 1	66.7	177	100	440	4500	4500	203	0.950	115	120.0	0.0885

产品性能参数及选型代码

额定速度	轴高	电机订货号	额定功率	额定转矩	额定电流	额定电压	最大可控转速	最大转速	堵转转矩	效率	堵转电流	额定频率	转动惯量		
n_{rated} rpm	SH mm	Order No.	P_{rated} Kw	M_{rated} Nm	I_{rated} A	U_{rated} V	$n_{max, inv}$ rpm	n_{max} rpm	M_0 Nm	η	I_0 A	F_{rated} Hz	J kgm ²		
进线电压:3相400V, 电源模块:Smart/Basic Line module															
1500	132	1PH8131-2□F2□ - □□□ 1	17.6	112	40	326	3150	4500	115	0.946	41	50.0	0.0446		
		1PH8133-2□F2□ - □□□ 1	23.1	147	42	371	2450	4500	155	0.947	43	50.0	0.0600		
		1PH8135-2□F2□ - □□□ 1	29.7	189	57	384	2650	4500	196	0.950	59	50.0	0.0750		
		1PH8137-2□F2□ - □□□ 1	32.7	208	58	371	2350	4500	226	0.951	60	50.0	0.0885		
		1PH8138-2□F2□ - □□□ 1	44.9	286	118	316	3500	4500	290	0.958	120	50.0	0.0885		
	160	1PH8164-2□F2□ - □□□ 1	59.0	375	111	380	2400	4000	440	0.940	118	100.0	0.1750		
		1PH8166-2□F2□ - □□□ 1	74.0	475	148	355	2600	4000	550	0.940	159	100.0	0.2160		
		1PH8168-2□F2□ - □□□ 1	84.0	530	169	355	2600	4000	620	0.940	179	100.0	0.2440		
		2000	132	1PH8133-2□G2□ - □□□ 1	30.6	146	57	383	3450	4500	155	0.950	61	66.7	0.0600
				1PH8135-2□G2□ - □□□ 1	39.0	186	81	346	3800	4500	196	0.952	85	66.7	0.0750
1PH8137-2□G2□ - □□□ 1	44.4			212	85	371	3500	4500	226	0.954	90	66.7	0.0885		
1PH8138-2□G2□ - □□□ 1	59.3			283	131	374	3900	4500	290	0.960	133	66.7	0.0885		
160	1PH8131-2□L2□ - □□□ 1		28.5	109	57	359	4500	4500	115	0.948	60	83.3	0.0446		
	1PH8164-2□L2□ - □□□ 1		88.0	335	165	355	4000	4000	440	0.955	205	167.0	0.1750		
	1PH8166-2□L2□ - □□□ 1		102	390	188	380	3900	4000	550	0.955	240	167.0	0.2160		
	1PH8168-2□L2□ - □□□ 1		119	455	225	355	4000	4000	520	0.955	240	167.0	0.2440		
	进线电压:3相400V, 电源模块:Active Line module														
	1750		132	1PH8131-2□F2□ - □□□ 1	20.4	112	40	377	3150	4500	115	0.947	41	58.3	0.0446
1PH8133-2□F2□ - □□□ 1		26.4		144	42	415	2450	4500	155	0.948	43	58.3	0.0600		
1PH8135-2□F2□ - □□□ 1		34.1		186	56	415	2650	4500	196	0.951	59	58.3	0.0750		
1PH8137-2□F2□ - □□□ 1		37.0		202	58	415	2350	4500	226	0.952	60	58.3	0.0885		
1PH8138-2□F2□ - □□□ 1		52.4		286	118	366	3500	4500	290	0.959	120	58.3	0.0885		
160		1PH8164-2□F2□ - □□□ 1	67.0	365	108	440	2400	4000	440	0.943	118	117.0	0.1750		
		1PH8166-2□F2□ - □□□ 1	85.0	460	143	410	2600	4000	550	0.943	159	117.0	0.2160		
		1PH8168-2□F2□ - □□□ 1	94.0	510	164	410	2600	4000	620	0.943	179	117.0	0.2440		
		2300	132	1PH8133-2□G2□ - □□□ 1	34.9	145	57	415	3450	4500	155	0.951	61	76.7	0.0600
				1PH8135-2□G2□ - □□□ 1	44.3	184	80	395	3800	4500	196	0.953	85	76.7	0.0750
				1PH8137-2□G2□ - □□□ 1	50.5	210	84	424	3500	4500	226	0.956	90	76.7	0.0885
				1PH8138-2□G2□ - □□□ 1	67.7	281	130	415	3900	4500	290	0.961	133	76.7	0.0885
2800	132	1PH8131-2□L2□ - □□□ 1	31.7	108	56	400	4500	4500	115	0.949	60	93.3	0.0446		
	160	1PH8164-2□L2□ - □□□ 1	93.0	315	156	395	4000	4000	440	0.959	205	187.0	0.1750		
		1PH8166-2□L2□ - □□□ 1	109	375	177	420	3900	4000	550	0.959	240	187.0	0.2160		
		1PH8168-2□L2□ - □□□ 1	123	420	210	395	4000	4000	520	0.959	240	187.0	0.2440		
进线电压:3相480V, 电源模块:Smart/Basic/Active Line module															
2000	132	1PH8131-2□F2□ - □□□ 1	23.2	111	39	427	3150	4500	115	0.948	41	66.7	0.0446		
		1PH8133-2□F2□ - □□□ 1	29	139	41	449	2450	4500	155	0.949	43	66.7	0.0600		
		1PH8135-2□F2□ - □□□ 1	37.9	181	56	449	2650	4500	196	0.952	59	66.7	0.0750		
		1PH8137-2□F2□ - □□□ 1	40.6	194	57	449	2350	4500	226	0.953	60	66.7	0.0885		
		1PH8138-2□F2□ - □□□ 1	59.7	285	118	416	3500	4500	290	0.960	120	66.7	0.0885		
	160	1PH8164-2□F2□ - □□□ 1	70	330	105	500	2400	4000	440	0.946	118	133.0	0.1750		
		1PH8166-2□F2□ - □□□ 1	89	425	138	465	2600	4000	550	0.946	159	133.0	0.2160		
		1PH8168-2□F2□ - □□□ 1	100	480	157	465	2600	4000	620	0.946	179	133.0	0.2440		
		2650	132	1PH8133-2□G2□ - □□□ 1	39.1	141	57	449	3450	4500	155	0.952	61	88.3	0.0600
				1PH8135-2□G2□ - □□□ 1	50.5	182	79	452	3800	4500	196	0.954	85	88.3	0.0750
				1PH8137-2□G2□ - □□□ 1	56.8	205	83	449	3500	4500	226	0.958	90	88.3	0.0885
				1PH8138-2□G2□ - □□□ 1	76.3	275	130	449	3900	4500	290	0.962	133	88.3	0.0885
3000	132	1PH8131-2□L2□ - □□□ 1	33.6	107	56	427	4500	4500	115	0.950	60	100.0	0.0446		
	160	1PH8164-2□L2□ - □□□ 1	96	305	150	420	4000	4000	440	0.960	205	200.0	0.1750		
		1PH8166-2□L2□ - □□□ 1	110	350	169	450	3900	4000	550	0.960	240	200.0	0.2160		
		1PH8168-2□L2□ - □□□ 1	125	395	197	420	4000	4000	520	0.960	240	200.0	0.2440		

永磁同步伺服电机

1PH8 同步伺服电机
水冷，防护等级 IP55

产品性能参数及选型代码

额定速度	轴高	电机订货号	额定功率	额定转矩	额定电流	额定电压	最大可控转速	最大转速	堵转转矩	效率	堵转电流	额定频率	转动惯量
n_{rated} rpm	SH mm	Order No.	P_{rated} Kw	M_{rated} Nm	I_{rated} A	U_{rated} V	$n_{max, inv}$ rpm	n_{max} rpm	M_0 Nm	η	I_0 A	F_{rated} Hz	J kgm ²
进线电压:3相400V, 电源模块:Smart/Basic Line module													
700	180	1PH8184-2□C2□ - □□□ 1	42	573	100	303	1450	3800	590	0.919	103	47	0.457
		1PH8186-2□C2□ - □□□ 1	58	791	142	295	1450	3800	800	0.924	143	47	0.599
	225	1PH8224-2□C2□ - □□□ 1	72	982	180	275	1450	3500	1007	0.947	183	47	1.28
		1PH8226-2□C2□ - □□□ 1	95	1296	255	255	1550	3500	1330	0.952	260	47	1.66
		1PH8228-2□C2□ - □□□ 1	121	1651	305	270	1450	3500	1680	0.955	306	47	2.02
1000	180	1PH8184-2□D2□ - □□□ 1	61	583	140	313	1950	3800	600	0.937	143	67	0.457
		1PH8186-2□D2□ - □□□ 1	80	764	190	300	2050	3800	800	0.943	196	67	0.599
	225	1PH8224-2□D2□ - □□□ 1	101	964	255	275	2050	3500	1007	0.956	262	67	1.28
		1PH8226-2□D2□ - □□□ 1	135	1289	325	285	1950	3500	1330	0.960	330	67	1.66
		1PH8228-2□D2□ - □□□ 1	169	1614	395	290	1950	3500	1680	0.962	408	67	2.02
1500	180	1PH8184-2□F2□ - □□□ 1	90	573	190	334	2700	3800	600	0.951	196	100	0.457
		1PH8186-2□F2□ - □□□ 1	119	758	275	305	2950	3800	800	0.952	285	100	0.599
	225	1PH8224-2□F2□ - □□□ 1	151	961	355	290	2900	3500	1007	0.962	367	100	1.28
		1PH8226-2□F2□ - □□□ 1	201	1280	445	305	2700	3500	1330	0.965	454	100	1.66
		1PH8228-2□F2□ - □□□ 1	251	1598	590	285	2900	3500	1680	0.964	612	100	2.02
2500	180	1PH8184-2□L2□ - □□□ 1	127	485	260	328	3800	3800	530	0.957	278	167	0.457
		1PH8186-2□L2□ - □□□ 1	168	642	370	305	3800	3800	720	0.957	405	167	0.599
	225	1PH8224-2□L2□ - □□□ 1	182	695	365	320	3500	3500	885	0.961	460	167	1.28
		1PH8226-2□L2□ - □□□ 1	228	871	400	360	3500	3500	1170	0.962	532	167	1.66
		1PH8228-2□L2□ - □□□ 1	270	1031	570	300	3500	3500	1400	0.963	762	167	2.02
进线电压:3相400V, 电源模块:Active Line module													
800	180	1PH8184-2□C2□ - □□□ 1	48	573	102	342	1450	3800	590	0.926	103	53	0.457
		1PH8186-2□C2□ - □□□ 1	66	788	142	335	1450	3800	800	0.931	143	53	0.599
	225	1PH8224-2□C2□ - □□□ 1	81	967	178	310	1450	3500	1007	0.952	183	53	1.28
		1PH8226-2□C2□ - □□□ 1	108	1289	255	287	1550	3500	1330	0.956	260	53	1.66
		1PH8228-2□C2□ - □□□ 1	138	1647	305	315	1450	3500	1680	0.958	306	53	2.02
1150	180	1PH8184-2□D2□ - □□□ 1	70	581	140	386	1950	3800	600	0.942	143	77	0.457
		1PH8186-2□D2□ - □□□ 1	92	764	190	345	2050	3800	800	0.948	196	77	0.599
	225	1PH8224-2□D2□ - □□□ 1	115	955	250	310	2050	3500	1007	0.959	262	77	1.28
		1PH8226-2□D2□ - □□□ 1	155	1287	325	325	1950	3500	1330	0.962	330	77	1.66
		1PH8228-2□D2□ - □□□ 1	194	1611	395	330	1950	3500	1680	0.964	408	77	2.02
1750	180	1PH8184-2□F2□ - □□□ 1	103	562	186	386	2700	3800	600	0.954	196	117	0.457
		1PH8186-2□F2□ - □□□ 1	138	753	275	355	2950	3800	800	0.955	285	117	0.599
	225	1PH8224-2□F2□ - □□□ 1	175	955	355	335	2900	3500	1007	0.963	367	117	1.28
		1PH8226-2□F2□ - □□□ 1	233	1271	440	355	2700	3500	1330	0.965	454	117	1.66
		1PH8228-2□F2□ - □□□ 1	289	1577	580	335	2900	3500	1680	0.965	612	117	2.02
2900	180	1PH8184-2□L2□ - □□□ 1	140	461	250	375	3800	3800	530	0.956	278	193	0.457
		1PH8186-2□L2□ - □□□ 1	178	586	340	345	3800	3800	720	0.955	405	193	0.599
	225	1PH8224-2□L2□ - □□□ 1	191	629	335	370	3500	3500	885	0.958	460	193	1.28
		1PH8226-2□L2□ - □□□ 1	238	784	365	413	3500	3500	1170	0.958	532	193	1.66
		1PH8228-2□L2□ - □□□ 1	283	932	520	345	3500	3500	1400	0.958	762	193	2.02

产品性能参数及选型代码

额定速度	轴高	电机订货号	额定功率	额定转矩	额定电流	额定电压	最大可控速度	最大转速	堵转转矩	效率	堵转电流	额定频率	转动惯量
n_{rated} rpm	SH mm	Order No.	P_{rated} Kw	M_{rated} Nm	I_{rated} A	U_{rated} V	$n_{\text{max, inv}}$ rpm	n_{max} rpm	M_0 Nm	η	I_0 A	F_{rated} Hz	J kgm ²
进线电压:3相480V，电源模块:Smart/Basic/Active Line module													
1000	180	1PH8184-2□C2□ - □□□ 1	60	573	102	423	1450	3800	590	0.937	103	67	0.457
		1PH8186-2□C2□ - □□□ 1	82	783	140	415	1450	3800	800	0.941	143	67	0.599
	225	1PH8224-2□C2□ - □□□ 1	101	964	178	385	1450	3500	1007	0.957	183	67	1.28
		1PH8226-2□C2□ - □□□ 1	134	1280	255	357	1550	3500	1330	0.960	260	67	1.66
		1PH8228-2□C2□ - □□□ 1	172	1642	300	390	1450	3500	1680	0.961	306	67	2.02
1350	180	1PH8184-2□D2□ - □□□ 1	82	580	140	417	1950	3800	600	0.946	143	90	0.457
		1PH8186-2□D2□ - □□□ 1	107	757	190	400	2050	3800	800	0.952	196	90	0.599
	225	1PH8224-2□D2□ - □□□ 1	135	955	250	365	2050	3500	1007	0.961	262	90	1.28
		1PH8226-2□D2□ - □□□ 1	180	1273	320	380	1950	3500	1330	0.964	330	90	1.66
		1PH8228-2□D2□ - □□□ 1	226	1599	395	395	1950	3500	1680	0.965	408	90	2.02
2000	180	1PH8184-2□F2□ - □□□ 1	110	525	176	434	2700	3800	600	0.957	196	133	0.457
		1PH8186-2□F2□ - □□□ 1	154	735	265	400	2950	3800	800	0.956	285	133	0.599
	225	1PH8224-2□F2□ - □□□ 1	186	888	330	380	2900	3500	1007	0.964	367	133	1.28
		1PH8226-2□F2□ - □□□ 1	248	1184	410	390	2700	3500	1330	0.965	454	133	1.66
		1PH8228-2□F2□ - □□□ 1	310	1480	550	380	2900	3500	1680	0.964	612	133	2.02
3200	180	1PH8184-2□L2□ - □□□ 1	142	424	230	405	3800	3800	530	0.954	278	213	0.457
		1PH8186-2□L2□ - □□□ 1	183	546	315	375	3800	3800	720	0.953	405	213	0.599
	225	1PH8224-2□L2□ - □□□ 1	196	585	310	400	3500	3500	885	0.954	460	213	1.28
		1PH8226-2□L2□ - □□□ 1	245	731	340	460	3500	3500	1170	0.954	532	213	1.66
		1PH8228-2□L2□ - □□□ 1	291	868	485	380	3500	3500	1400	0.954	762	213	2.02